



Material Safety Data Sheet

Section 1. Chemical Product and Company Identification

Product name Smoke Odor Eliminator
Product code ZU018719
Date of issue 03/14/11 **Supersedes** 10/19/07

Emergency Telephone Numbers

For MSDS Information:
 Compliance Services 404-352-1680

For Medical Emergency
 (877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
 CHEMTREC: (800) 424-9300 - All Calls Recorded
 In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
 1420 Seaboard Industrial Blvd.
 Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

WARNING

CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.
 HARMFUL OR FATAL IF SWALLOWED.
 CONTENTS UNDER PRESSURE.

*Hazard Determination System (HDS): Health, Flammability, Reactivity



NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Inhalation.

- Eyes** Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.
- Skin** May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.
- Inhalation** Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation. Inhalation of spray mists or vapors may cause central nervous system depression characterized by headache, dizziness, nausea, and/or stupor.
- Ingestion** May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Prolonged or repeated contact may dry skin and cause irritation.

Carcinogenicity No known significant effects or critical hazards.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients


| Name of Hazardous Ingredients | CAS number | % by Weight |
|--|------------------|-------------|
| HYDROCARBON PROPELLANT; blend of propane & isobutane | 75-28-5; 74-98-6 | 20 - 30 |
| ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum) | 64741-73-7 | 10 - 20 |
| TRIETHYLENE GLYCOL; 2,2'-ethylenedioxyethanol; TEG | 112-27-6 | 1 - 5 |

Section 4. First Aid Measures

- Eye Contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
- Skin Contact** Flush affected skin with plenty of water. Get medical attention if irritation develops.
- Inhalation** Move exposed person to fresh air. If irritation persists, get medical attention.
- Ingestion** Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



| | |
|---------------------------------|---|
| Flash Point | Not available. |
| Flammable Limits | Not available. |
| Flammability | Non-flammable. (CSMA Method) |
| Fire hazard | CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Bursting aerosol containers may be propelled from a fire at high speed. |
| Fire-Fighting Procedures | Use an extinguishing agent suitable for the surrounding fire. Cool closed containers exposed to fire with water. Fire-fighters should wear appropriate protective equipment. |

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

| | |
|-----------------|--|
| Handling | Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Observe label precautions. Wash thoroughly after handling. |
| Storage | CONTENTS UNDER PRESSURE. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Keep out of the reach of children. |

Section 8. Exposure Controls/Personal Protection**Product name**

HYDROCARBON PROPELLANT; blend of propane & isobutane
ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum)

Exposure limits

ACGIH TLV / OSHA PEL (United States). Notes: Propane
TWA: 1000 ppm 8 hour(s).
NIOSH REL (United States).
TWA: 1200 mg/m³ Form: Vapor

Personal Protective Equipment (PPE)

| | |
|--------------------|---|
| Eyes | Safety glasses. |
| Body | For prolonged or repeated handling, use the following type of gloves: Neoprene gloves. Nitrile gloves. Rubber gloves. |
| Respiratory | Use with adequate ventilation. |

**Section 9. Physical and Chemical Properties**

| | | | |
|-------------------------|---|-------------------------|--------------------------------|
| Physical State | Liquid. [Aerosol.] | Color | Opaque. Emulsion. |
| pH | Not applicable | Odor | Pleasant. |
| Boiling Point | Not determined. | Vapor Pressure | Not determined. |
| Specific Gravity | 0.92 | Vapor Density | Not determined. |
| Solubility | Very slightly soluble in the following materials: cold water and hot water. | Evaporation Rate | <1 (Water = 1) |
| | | VOC (Consumer) | 228 (g/l). 1.9 lbs/gal (24.9%) |

Section 10. Stability and Reactivity

| | |
|---|--|
| Stability and Reactivity | The product is stable. |
| Incompatibility | Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials. |
| Hazardous Polymerization | Will not occur. |
| Hazardous Decomposition Products | carbon oxides (CO, CO ₂) |

Section 11. Toxicological Information**Acute Toxicity**

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|-------------|---------|-------------|----------|
| Isoparaffinic Solvent; Hydrotreated light distillate (petroleum) | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Oral | Rat | >2000 mg/kg | - |

Section 12. Ecological Information

Environmental Effects No known significant effects or critical hazards.

Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Non-hazardous waste

Section 14. Transport Information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label |
|---------------------------|-----------------|----------------------|---------|-----|-------|
| DOT Classification | Not regulated. | Consumer commodity | ORM-D | | |
| TDG Classification | Not determined. | | | | |
| IMDG Class | Not determined. | | | | |

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

[All Components of this product are listed or exempt from listing on TSCA Inventory.](#)

United States inventory (TSCA 8b): Not determined.

State Regulations

California Prop 65 No products were found.

Canada**WHMIS (Canada)**

Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

Class D-2B: Material causing other toxic effects (Toxic).

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.